

HHEX-K series UPS 600/650/1000/1200VA



Technical specification:

Model		HHEX-K-500/600	HHEX-K-650/800	HHEX-K-1000/1200
MAX capacity (VA)		600VA(360W)	650VA(390W)	1000VA(600W)
Rated capacity(VA)		500VA(300W)	800VA(480W)	1200VA(720W)
Input	Commercial power range	140VAC-280VAC		
	AVR range	155VAC-276VAC		
	Frequency	50Hz±10%		
	Commercial power	Sine-wave		
Output	Inversion	Simulated sine-wave		
	Frequency	50/Hz±0.5(auto-sensing)		
	AVR	220VAC±10%(auto-sensing)		
	Transfer time	Typical 4-6ms		
Protection	Spike protection	320 joules, 2ms		
	Filter	10dB at 0.15 Hz , 50dB at 30 Hz		
	Overload	UPS automatic shutdown if overload exceeds 110% of normal value for 30 seconds and 130% for 3 seconds		
	Short circuit	UPS output is cut off immediately or input circuit breaker protection		
Alarm	Battery back-up	Beeping sound every 4 seconds		
	Battery low voltage	Beeping sound every 1 seconds		
	Overload	Continuous beeping sound		
Battery	Type	Sealed maintenance-free lead acid		
	Capacity	1X (12V, 7AH)	1X (12V, 7AH)	2X (12V, 7AH)
	Recharge time	8 hours to 90% of full capacity		

	Back-up time	Typical 20 min(half)		
	Battery protection	Automatic self-test, discharge protection		
Appearance	Net weight	7Kg	8Kg	13.0Kg
	Gross weight	7.5Kg	8.5Kg	13.5Kg
	Size D×W×H	320×110×160	320×110×160	375×130×190
Outside Packing	Weight	30Kg	34Kg	28.5Kg
	Quantity	4	4	2
	Size(mm)D*W*H	465x365x470	465x365x470	495x460x315
Remark	Specification only for reference. Subject to change without prior notice			
	We accept order with special specifications			



Hunterhex AB (Ltd's)
 EMEA Sweden
 APAC & SEA Hong Kong
 Factories SEA

E-mail: sales@hunterhex.com
 Phone Sweden: +46(0)705816424
 Phone Americas: +1 339 244 2118
 Phone UK: +44 7937 013 692

Web: www.hunterhex.com