

POWER

# PORTABLE POWER

HHEX-PRIME / 450-620-750



# PRODUCT OVERVIEW

## Portable Power

HHEX-PRIME Portable Power series offers highly versatile and portable power supply solutions, powering equipment, devices home or outdoors, convenient and easy to use. It can also be a critical power source and in the event of an emergency. Ideal for camping, tailgating and other activities where power is not available or convenient.

HUNTERHEX PRIME Portable Power is reliable portable power for your lifestyle and safety.

Stay with PRIME portable power, stay powered and entertained everywhere!

### Feature & benefits

- **Rugged Construction**  
-Reliable performance in harsh conditions.
- **All-in-one Operation**  
With AC & solar inputs as well as outlets for both AC & DC power, Prime Portable Power can master numerous tasks for extended periods.
- **Long Life**  
Advanced li-ion cells along with other quality components allow Prime Portable Power to deliver a long service life.
- **Go Anywhere**  
Lightweight, compact & reliable.
- **Silent Renewable Energy**  
The benefits of a generator without the noise and fuss.



USA-MEX  
CAN & JPN



GBR-LRL  
MLT  
MAS & SIN



AUS-NZL  
ARG & CHN



EUROPE  
ASIA  
AMERICA

### Contact Details

T. +46 763 916 550

info@hunterhex.com  
sales@hunterhex.com

HUNTERHEX AB  
EMEA Office  
Färögatan 33  
SE-164 51 Kista  
Sweden

# SPECIFICATION

## LOADING TIME (Approximate)

	ITEM	PRIME 450	PRIME 620	PRIME 750
Battery	Battery Type	Li-ion battery (NMC)		
	Battery Capacity	477 Wh (11.1 V 43Ah)	635 Wh (11.1 V 57.2 Ah)	788 Wh (11.1 V 71 Ah)
	Cycle Life	>1500		
Input	AC Wall Charging	12.6 V 5 A	12.6 V 5 A	12.6 V 7.5 A or 12.6 V 10 A
	Solar Charging	12.5 V ~ 25 V / Max. power up to 125 W		
※ AC Output (Pure Sine Wave)	Total Port	2 × AC ports		
	Rated Power	300 W	300 W	500 W
	Pulse Power	1500 W	1500 W	2500 W
	Voltage/Frequency	230 V/50 Hz; 110 V//60 Hz		
DC Output	USB Port	1 × 5 V 1 A 1 × 5 V 2 A 1 × 5 V 2.4 A (Fast Charge)		
	Cigarette Lighter Socket	1 × 12 V / 60 W (Max. 96 W)		
	DC Port	2 × 12 V 2.5 A		
LED Lighting	Multi-mode	High Bright (100% power) Normal (50% power) Energy Saving (25% power) Emergency Flash SOS Signal		
General	Dimensions (L × W × H)	349 × 160 × 285 mm (13.7 × 6.3 × 11.2 inch)		
	Net Weight	6 kg (13.2 lbs)	6.8 kg (15 lbs)	7.5 kg (16.5 lbs)
	Working Temperature	Discharge Temperature: -10 to 45°C (14 to 113°F) Charge Temperature: 0~45°C (32 to 113°F)		
	Certification	RoHS, CE, FCC, RCM, PSE, CEC		

DEVICES	PRIME 450	PRIME 620	PRIME 750
3W Lighting	140h+	190h+	230h+
MP3 Player Recharges	300X+	410X+	500X+
Playstation Recharges	50X+	70X+	90X+
Camera Recharges	90X+	130X+	160X+
Smartphone Recharges	40X+	50X+	70X+
Tablet Recharges	10X+	14X+	17X+
Laptop Recharges	4X+	6X+	8X+
60W Fan	7h+	9h+	12h+
TV	4h+	5h+	7h+
Mini Bar	9h+	12h+	15h+
Tooling Up To 500W	N/A	N/A	1~1.5h

